





REV	DESCRIPTION	DATE	APPROVE
P1	PRELIMINARY	24/03/27	QYJ



MOTOR PARAMETERS @25°C		
	UNITS	VALUE
Supply Voltage(reference) (Vs)	VDC	48
Rated Continuous Torque (Tcr)	Nm	1.31
Rated Speed at Cont.Torque (Scr)	R.P.M.	3000
Rated Continuous Stall Current (Ics)	A	16.93
Rated Continuous Output Power (Po.c)	W	411
Motor Constant (Km)	Nm/√w	0.2030
Torque Constant (KT)	Nm/A	0.0812
Voltage Constant (KE)	Vrms/krpm	8.0
Terminal Resistance (Rmt)	ohms	0.25
Inductance (L)	mH	0.45
Rated Peak Current (Ipr)	A	57.88
Rated Peak Torque (Tpr)	Nm	4.50
Coulomb Friction Torque (Tf)	Nm	0.0470
Insulation Class		F
Rotor Inertia (Jr)	Kg.m <sup>2</sup>	1.2E-04
Motor Weight (Wm)	Kg	2.1
Feedback Device		2500p/rev incremental encoder



8 Pole Motor

ENCODER CONNECTIONS		
PIN	COLOR	SIGNAL
1	BLU	A+
2	GRN	B+
3	BLK	GND
4	GAY	W+
5	BRN	U+
6	BRN/BLK	U-
7	YEL	Z+
8	YEL/BLK	Z-
9	WHT	V+
10	WHT/BLK	V-
11	BLU/BLK	A-
12	GRN/BLK	B-
13	RED	+5v
14	GAY/BLK	W-
15	NC	NC

MOTOR CONNECTIONS		
	COLOR	SIGNAL
	YEL	U
	GRN	V
	BLUE	W
	YEL/GRN	GND

NOTE: THIS DRAWING HAS BEEN CREATED BY AUTOCAD. MANUAL REVISIONS ARE NOT ALLOWED.

MATERIAL		TOLERANCE UNLESS OTHERWISE SPECIFIED ISO 2768-1 MEDIUM			
DRAWN XXX	CHECKED	APPROVED - DATE	FILENAME	DATE XX/XX/XX	SCALE N/A
			BRUSHLESS SERVO MOTOR		
			SV080AS-01		SHEET 1/1

This drawing and the information disclosed herein are proprietary data of Mach Motion Products, and is to be immediately returned upon request. Reproduction of this drawing or the information contained herein is prohibited without the expressed written approval of Mach Motion Products.