Frame size	mm	60
Gear Ratio	i	5
Rated output torque	Nm	19
Max output torque	Nm	19
Max radial load	N	1200
Max axial load	N	1050
Max input speed	RPM	10000
Noise Level	dB(A)	≤ 60
Backlash	arcmin	≤ 10
Operating temp.	°C	-25~90
Lifetime	Hrs	20000
Efficiency	%	≥ 96
Degree of protection		IP 64
Mounting position		Any





UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN mm
ALL ANGLES ±0.5°
BREAK ALL EDGES 0.2mm~0.8mm
DECIMALS .X ±0.2 / .XX ±0.05
T.I.R. ◎ 0.05 ⌖ 0.05 ⫽ 0.05

Proprietary And Confidential
The information contained in this drawing is the sole property of Mach Motion Products, any reporduction in part or as a whole wihtout the written permission of Mach Motion Products is prohibited

	DATE	NAME
DRAWN	2018.04.27	TERESA CHANG
CHECKED		
APPROVED		

MATERIAL:
HEAT TREATMENT:
FINISH:

Mach Motion Products

TITLE	60 Type Planetary Gearhead 5:1
PART NO.	MPS-60-005-10-SMA
DWG.NO.	
NOTE	
SCALE	1:1.5
SHEET	
REV	0