	1	2	1	3	4	1	5	; [6	7 8
	Frame size		mm	60						
А	Gear Ratio		i	3						
	Rated output torque		Nm	19						A
	Max output torque		Nm	19						
	Max radial load		Ν	1200						
	Max axial load		Ν	1050						
	Max input speed		RPM 10000							00
В	Noise Level		dB(A)	≤60						E
	Backlash		arcmin	≤6						
	Operating temp.		°C	-25~90						
	Lifetime		Hrs	20000						
	Efficiency		%	≥96						
	Degree of protection			IP 64						
С	Mounting position			Any						<u>5.0</u> C
D	B9 B9 B9 B9 B9 B9 B9 B9 B9 B9									
BREAK ALL EDGES 0.2mm~0.8mm DECIMALS X ±0.2/XX ±0.05								60 Type Planetary Gearhead 3:1		
F				PROPRIETARY AND	CONFIDENTAL		DATE	NAME	PART NO	. MPS-60-003-06-LMA F
			SC	IE INFORMATION CONTAINED DLE PROPERTY OF MACH MO PRODUCTION IN PART OR AS IE WRITTEN PERMISSION OF	FION PRODUCTS, ANY A WHOLE WITHOUT	CHECKED	2018.03.06		DWG.NO	
	1	2	is	PROHIBITED 3	4	APPROVED	5		 6	SCALE 1:1.5 SHEET REV 1 7 8